(FILE 'USPAT' ENTERED AT 14:55:48 ON 10 MAR 93)

```
L1             72 S GUARD SIGNAL
L2            617 S TRANSITION DETECTOR
L3              0 S L1 AND SIGNAL SAMPLES
L4             16 S L2 AND SIGNAL SAMPLES
L5              4 S L4 AND EQUIVALENT

=> d 15 1-4
```

1. 4,777,385, Oct. 11, 1988, Signal transient improvement circuit; Werner N. Hartmeier, 307/263, 517; 328/55, 109

2. 4,041,456, Aug. 9, 1977, Method for verifying the denomination of currency; David M. Ott, et al., 382/7; 209/534; 382/30

3. 3,882,540, May 6, 1975, Readback circuits for digital signal recorders; Hjalmar H. Ottesen, 360/39

4. 3,727,136, Apr. 10, 1973, AUTOMATIC EQUALIZER FOR PHASE-MODULATION DATA TRANSMISSION SYSTEMS; Henry Charles Schroeder, et al., 375/15; 333/18, 28R; 375/83

=>

10. 3,681,530, Aug. 1, 1972, METHOD AND APPARATUS FOR SIGNAL BANDWIDTH COMPRESSION UTILIZING THE FOURIER TRANSFORM OF THE LOGARITHM OF THE FREQUENCY SPECTRUM MAGNITUDE; Harold J. Manley, et al., 395/2; 381/32, 41

=> dis his

(FILE 'USPAT' ENTERED AT 14:55:48 ON 10 MAR 93)
DEL HIS
L1 324342 S (REGISTER OR STORAGE)

L2 1652 S L1 AND SIGNAL SAMPLES
L3 10 S L2 AND SAMPLE COMPARISON

=> s l3 and encode?
42638 ENCODE?
L4 3 L3 AND ENCODE?

=> d l4 1-3

1. 4,282,411, Aug. 4, 1981, Residual echo suppressor for echo canceller; Robert C. Stewart, 379/406

2. 4,150,368, Apr. 17, 1979, Signal coding for compressed pulse code modulation system; Ramon C. W. Chea, Jr., 341/108, 138 [IMAGE AVAILABLE]

3. 3,681,530, Aug. 1, 1972, METHOD AND APPARATUS FOR SIGNAL BANDWIDTH COMPRESSION UTILIZING THE FOURIER TRANSFORM OF THE LOGARITHM OF THE FREQUENCY SPECTRUM MAGNITUDE; Harold J. Manley, et al., 395/2; 381/32, 41

=>

```
=> s (register or storage)
         93915 REGISTER
        269888 STORAGE
L1      324342 (REGISTER OR STORAGE)

=> s l1 and signal samples
        376074 SIGNAL
        136769 SAMPLES
          2357 SIGNAL SAMPLES
                 (SIGNAL(W)SAMPLES)
L2        1652 L1 AND SIGNAL SAMPLES

=> s l2 and sample comparison
        188987 SAMPLE
        237454 COMPARISON
           103 SAMPLE COMPARISON
                 (SAMPLE(W)COMPARISON)
L3          10 L2 AND SAMPLE COMPARISON

=> d l3 1-10

1.  5,053,983, Oct. 1, 1991, Filter system having an adaptive control for
updating filter samples; Gilbert P. Hyatt, 364/724.03, 724.04, 724.18
[IMAGE AVAILABLE]

2.  5,022,074, Jun. 4, 1991, Digital echo suppressor; David C. Nicholas,
379/407; 370/32.1; 379/406 [IMAGE AVAILABLE]

3.  4,602,276, Jul. 22, 1986, Digital signal level overload system;
Russell T. Fling, et al., 358/27

4.  4,491,930, Jan. 1, 1985, Memory system using filterable signals;
Gilbert P. Hyatt, 364/602, 726

5.  4,282,411, Aug. 4, 1981, Residual echo suppressor for echo canceller;
Robert C. Stewart, 379/406

6.  4,267,593, May 12, 1981, Method and means for digital conferencing;
John F. Regan, et al., 370/62

7.  4,246,652, Jan. 20, 1981, Seismic source signatured evaluation
apparatus; Tawassul A. Khan, et al., 367/42; 364/421; 367/47 [IMAGE
AVAILABLE]

8.  4,209,843, Jun. 24, 1980, Method and apparatus for signal enhancement
with improved digital filtering; Gilbert P. Hyatt, 364/728.03, 517 [IMAGE
AVAILABLE]

9.  4,150,368, Apr. 17, 1979, Signal coding for compressed pulse code
modulation system; Ramon C. W. Chea, Jr., 341/108, 138 [IMAGE AVAILABLE]
```

L1 4 "WHITTINGTON, CHARLES L"/IN

=> d l1 1-4

1. 5,123,014, Jun. 16, 1992, Data link with an imbedded channel; John C. Federkins, et al., 370/110.1; 379/59, 60; 455/33.1 [IMAGE AVAILABLE]

2. 4,918,572, Apr. 17, 1990, Modular electronic package; Carl R. Tarver, et al., 361/736, 683; 439/377, 928; D14/100, 109 [IMAGE AVAILABLE]

3. 4,719,567, Jan. 12, 1988, Method and apparatus for limiting bus utilization; Charles L. Whittington , et al., 395/325; 364/240, 240.5, 242.6, 242.92, 264, 264.4, DIG.1 [IMAGE AVAILABLE]

4. 4,473,878, Sep. 25, 1984, Memory management unit; John E. Zolnowsky, et al., 395/400; 364/229, 229.2, 238.4, 244, 244.6, 246, 246.3, 247, 247.4, 247.8, 253, 253.1, 255.1, 255.5, 256.3, 256.5, 259, 259.2, 259.7, 263, DIG.1 [IMAGE AVAILABLE]

=> d l1 3 ab

US PAT NO: 4,719,567 [IMAGE AVAILABLE] L1: 3 of 4

ABSTRACT:
A bus master is prevented from utilizing a communication bus during a current sample interval if the utilization rate of the communication bus during the immediately preceeding sample interval exceeded a selected limit.

=> L